

John Wilkie Paper Mill Services Ltd
Maryfield, Manse Lane St Fillans Perthshire UK PH6 2NF
Tel 0044 (0)1764 685267 email jw@wilkiemaryfield.co.uk
www.johnwilkiepms.co.uk


In Conjunction with
Hilco Global APAC
Tel 0061 412 389090 email: ascharer@hilcoglobal.com

MG PAPER MACHINE WITH REWINDER 4650 mm

Directors: John Wilkie, Christine Wilkie B.Sc. B.Acc.(Hons), C.A.
Registered in Scotland: No. SC 254554 Vat No. GB 827444418

John Wilkie Paper Mill Services Ltd
Maryfield, Manse Lane St Fillans Perthshire UK PH6 2NF
Tel 0044 (0)1764 685267 email jw@wilkiemaryfield.co.uk
www.johnwilkiepms.co.uk

PM2 PAPER MACHINE



Directors: John Wilkie, Christine Wilkie B.Sc. B.Acc.(Hons), C.A.
Registered in Scotland: No. SC 254554 Vat No. GB 827444418



Control system on machine

The QCS/DCS is a Valmet system. Majority is CAN and DNA hardware which has been progressively upgraded since 2000.

Drive

DC sectional drive by Siemens model 6RA 70 installed 2001, gear drive.

Approach flow

Large Masson Scott conical refiner (not in use).

Selective refining, SW refining one 16" G L V disc refiner 4000 series, manual loading. 1 t/hr capacity, 500 ltr/min.

Masson Scott midget conical refiner (not in use). Manual loading.

HW refiner JCO3 Valmet conical refiner, auto loading.

HW refiners two 46" Sutherland Atmospheric disc refiners with auto loading.

HW capacity 6,000 ltrs/min, 4 t/hr/capacity specific ref 690 kwh.

Back water/wire pit recovery by a rectangular Sveen Saveall air flotation unit with surface scrappers for recovered fibre.

Four drum thickeners with stainless tanks and central drum, for long fibre, B fibre, Eucalyptus and broke.

Stock Preparation Cleaning

Noss 4 stage L/D cleaner system. Cascade type in four stages. No recovery system,

Machine pressure screens two Beloit Centriscreens model 10 stainless steel. Slotted baskets 0.35mm slots.

Primary and secondary fan pumps.

Paper machine Beloit Walmsley. MG

Basement machine with drive on left from the flowbox. year 1956, last major rebuild/overhaul 2018.

Production 30,000 t/year

t/hr at 44gsm 5t/hr.

Total width 5016 mm.

John Wilkie Paper Mill Services Ltd

Maryfield, Manse Lane St Fillans Perthshire UK PH6 2NF

Tel 0044 (0)1764 685267 email jw@wilkiemaryfield.co.uk

www.johnwilkiepms.co.uk

Production width 4650mm.
Maximum production speed 500m/min.
Mechanical speed Range 550 m/min balance.
Product light weight bag kraft.
Grammage range 27 to 100 gsm.
Pulp type OCC/Pine/Eucalyptus
Production in 2022: 25,623 t, two breaks / day, 73tons working day average.
Stainless hog pit chest
Dry end stainless pulper under pope with infeed tray from roll splitter.

Flowbox

PMP flowbox type intelijet V, stainless steel with a diffuser, the flowbox has had recently fitted slice lip profile control PMP Intel. Adjustable jacks, CD weight control, slice lip 5016 mm, 50 slice actuators, zone width 50mm, consistency 0.2%, flow 35,000 l/min. Pressurized with recent slice control equipment..

Wire section

Wire section: run out type. No wire shake, dewatering comprising forming board, two foil boxes with smart foils, four foil boxes with gravity foils, one low vacuum Albany unifoil unit, four vacuum boxes each with eight chambers.

Wire frame: stainless with some cast and fabricated parts. Breast roll to couch roll: centres 17 mtrs. Suction couch cantilevered with top felted lump breaker roll. Judd wire guide. Dry content after wire section: 19%.

Press sections

Type open draw straight through press

Press max load kN/m 35/55/35

Dry content after third press 32%

First open draw couch to first press

Suction press roll with r/cover 1st press ceramic top roll with spare rubber covered top roll.

2nd press composite cover with Top Rock covered top roll

3rd press rubber covered

Video monitoring on presses for breaks.

Dryer Section

Pre dryers, steam pressure 3.8 bars.

Mixture of A/F and oil ring bearings

Diameter 1830mm

Rotary syphons for condensate


Pre dryers 15 conventional

Enclosed gear drive

Moisture content after pre-drying 4-6%

Directors: John Wilkie, Christine Wilkie B.Sc. B.Acc.(Hons), C.A.

Registered in Scotland: No. SC 254554 Vat No. GB 827444418



John Wilkie Paper Mill Services Ltd

Maryfield, Manse Lane St Fillans Perthshire UK PH6 2NF

Tel 0044 (0)1764 685267 email jw@wilkiemaryfield.co.uk

www.johnwilkiepms.co.uk

Cooling cylinders 6 out of service

Monitoring systems are for moisture after the MG and reel up

MG cylinder

Sandusky Walmsley cast iron cylinder

Shell diameter 4267mm (14 ft).

Maximum roll load 100 Kn/m

Designed maximum pressure 6.9 bar

Year of manufacture 2001

Single press roll pneumatic loading rubber covered

Anti-friction roller bearings

MG as supplied and tested 2022 and first regrind was completed.

MG Hood

Gas burner air heated

Winterburn manufacture

Dry and wet end fans

Dry and wet end burners. Wet end burner in service.

Post dryers

4 conventional type.

Anti-friction bearings.

Enclosed gear drives.

Cross machine scanner

Valmet IQ scanner measuring:

Profile, Gsm, Caliper, Moisture.

WebVision WIS

Reel up

Black Clawson horizontal reel up, web change system TUSA 1VTape Turnup

Width at pope: 4650mm

Pneumatic operation

Pneumatic tail transfer

To left side of machine house: a roll splitter feeding into the stainless dry end pulper.

Machine Drive

DC sectional electric drive, Siemens model 6 RA 70 installed 2001.

Directors: John Wilkie, Christine Wilkie B.Sc. B.Acc.(Hons), C.A.

Registered in Scotland: No. SC 254554 Vat No. GB 827444418

Vacuum system

Nash 900 series, located to outside of the machine house.
Three Nash vacuum pumps for felt conditioning in the basement.
Two Nash vacuum pumps for the suction boxes in the basement.

Rewinder

Beloit rewriter, year 1956, single shaft type unwind with brake and motor
Working width 4560mm.
Capacity 50 reels/hr
Minimum reel width 2600mm
Plastic wrap
11 manual settings slitters, bottom slitters with individual drives.
Main drive individual motors to each drum.
Drive on right side from the unwind.
Cores 3 to 5"
Reel transport by Lamb slat conveyor floor mounted.
Rewind maximum diameter 1530mm, minimum 500mm.

Reel packer

Lamb reel packer, Year 1956, capacity 50 reels/hr.
Maximum reel width: 2560mm/ minimum reel width 300 mm.
Minimum reel diameter: 1530mm

Rebuilds

1969 open headbox to hydraulic rectifier headbox
1975 second press upgrade
1985 MG hood replacement
2000 VIB installation
2000 Siemens drive upgrade
2002 MG cylinder upgrade
2018 headbox upgrade
2019 CD Weight control/WIS upgrade
2020 Refining upgrade/ HV Switchboard upgrade
2022 LV Switchboard upgrade.

SECTION 3 IN MILL DETAILS

PULPER

Pulper for trim number 2, Broke pulper year 1997, with core link core stripping unit, conveyor system, capacity 19.5 m³, production 2.5 to 3.3 t/day, and outside pulper, stainless low consistency pulper, Number O9P10.

CUT SIZE LINE



Sheeters (CSS3)

ECH Will A4/A3 sheeter, 12 pockets, six double floor pick up unwinds, edge guiding, tension control, decurling section, synchro cut, model SLK470U, serial number 07749, year 1991. reject gate. Grammages: cut 70,75 and 80, maximum operating speed 350 m/min, gripper cycles/min 13.75 and layboy for 12 pockets when cutting A4 size. This sheeter with two packing lines.

Packaging line number one (CSS3)

Pemco/Robotic Automation
year 1994
sheet size A4
wrapper speed 140 reams/min
cartoniser maximum speed 115 reams/min
accumulator maximum speed 100 reams/min

Packaging line number two (CSS3)

Pemco/Robotic Automation
year 1994
sheet size A4/A3
wrapper speed 120 reams/min
cartoniser maximum speed 115 reams/min
accumulator maximum speed 100 reams/min
robot maximum speed 100 reams/min

Bulk packer (CSS3)

Pemco
Year 2000
Cartoniser maximum speed 45 reams/min
Accumulator 45 reams/min

Pallet Line (CSS3)

Make Robotic Automatic
Year 1994
Film wrap speed 21 pallets/hr

Pallet Line number three (CSS5)

Make Robotic Automatic
Year 1998
Sheet size A4 and US letter
Wrapper maximum speed 140 reams/min
Cartoniser maximum speed 125 reams/min
Accumulator maximum speed 120 reams/min
Robot maximum 100 reams/min

Packaging line number 4 (CSS5)

Make Robotic Automatic
Year 2000
Sheet size A4 and US letter
Wrapper maximum speed 140 reams/min

Cartoniser maximum speed 125 reams/min
Accumulator maximum speed 120 reams/min
Robot maximum 100 reams/min

CSS Pallet line (CSS5)

Make Robotic Automation

Year 1998

Film wrapper speed, dom,pallets/hr 34

SHEETER CSS5




Sheeter complete with two lines for paper wrapping, labelling, ream collator, two box lines, conveyor to pallet stacker.

Will A4/A3 sheeter, 12 pockets, six double floor pick up unwinds, edge guiding, tension control, decurling section, model 260/12/R, Serial number 97H79720 , year 1997.

Sheeter complete with line for paper wrapping, labelling, ream collator, two box lines, conveyor to pallet stacker.

Hydra Pak horizontal baler with auto wire tying for sheeter trim.



John Wilkie Paper Mill Services Ltd

Maryfield, Manse Lane St Fillans Perthshire UK PH6 2NF

Tel 0044 (0)1764 685267 email jw@wilkiemaryfield.co.uk

www.johnwilkiepms.co.uk

JAGENBERG REWINDER



Salvage rewriter Jagenberg VariDur, width 2770mm on knife shaft, Unwind Jagenberg: inclined floor pick up, shaftless with individual disc brakes, tension control, various core chucks, 10 slitters manual setting, core feeder, shaftless rewind 1800mm diameter. Twin motor drive, reel ejector and lowering table. Year 1996, number AW236`2, TYPE 45U5 - 2600.

BRITISH REWINDER U2A



Directors: John Wilkie, Christine Wilkie B.Sc. B.Acc.(Hons), C.A.

Registered in Scotland: No. SC 254554 Vat No. GB 827444418

John Wilkie Paper Mill Services Ltd

Maryfield, Manse Lane St Fillans Perthshire UK PH6 2NF

Tel 0044 (0)1764 685267 email jw@wilkiemaryfield.co.uk

www.johnwilkiepms.co.uk



British rewriter model U2A, Shaftless Langston floor pick up unwind, year early 1960s, design speed 1220 m/min, operating speed 700 m/min, unwind reel width 2700mm, rewind width 2600mm untrimmed. Narrowest reel width 120mm, diameter rewind 1530mm, min diameter rewind 650mm, 10 slitters manual setting, core sizes 3 and 8 inches.

PULPER

PM1 Black Clawson pulper, volume 19 m3, year 1994, for reel core broke, core link reel stripper, number 09P08, conveyor for paper removed from cores, Stainless steel batch pulper . Capacity 4 to 6 t/d.

THIS INFORMATION IS THE TITLE OF JOHN WILKIE PAPERMILL SERVICES LTD AND SHOULD NOT BE COPIED OR FORWARDED TO A THIRD PARTY WITHOUT CONSENT.

FOR YOUR GENERAL INFORMATION WE HAVE TO INTIMATE THE FOLLOWING TO YOU:

No warranty being given to the accuracy of any measurements, specifications or other details whatsoever given within the schedule. Whilst every reasonable effort has been made to verify any statement, description, or comment made within this schedule, for the avoidance of doubt it is emphasised have not been able to be verified.

Directors: John Wilkie, Christine Wilkie B.Sc. B.Acc.(Hons), C.A.

Registered in Scotland: No. SC 254554 Vat No. GB 827444418